



TWILIGHT

Unique and spacious

Twilight sets new standards for the future of glamping that will set your site apart from other campsites and holiday parks. The newly designed roof structure gives your guests an extra spacious feel.

With a robust hardwood frame and a steel-constructed roof, the Twilight can withstand the toughest conditions – including wind gusts of up to ten on the Beaufort scale. Whilst we hope your guests enjoy sunny, cloudless days, we promise they will stay safe whatever the weather.

This canvas lodge has a modular system, allowing you to choose from different wall materials and window sizes, with the flexibility to arrange the space depending on your needs. Therefore, you can choose the look and feel that matches your campsite or holiday park.

- ✓ Unique and stylish design. It has the “wow factor” and will make your site stand out.
- ✓ Modular system and options for extra flexibility in layout.
- ✓ A sturdy “truss” subframe for increased strength and a roof edge fitted with steel cable tensioning.
- ✓ Special corner tensioners designed for a perfectly secure fit.



FLOORPLAN TWILIGHT

Dimensions

Inner tent	304.6 ft	15.7 x 19.4 ft
Veranda	124.0 ft ²	15.7 x 7.9 ft
Total surface	427.0 ft ²	15.7 x 27.2 ft
Footprint	546.0 ft ²	18.7 x 29.2 ft

Features

# Guests	4
# Bedrooms	2
Bathroom	Yes
Kitchen	Yes

Floorplan 3D



Floorplan 2D



PHOTOS TWILIGHT



SPECIFICATIONS TWILIGHT

Elements	Colour	Specifications	Technical standards
PVC Roof	Grey Beige Brown Green	UV and flame retardant PVC 650gr/m ² . The PVC is easy to clean and meets the stringent European, British and American fire regulations (M2, B1 and DIN 4102 standard).	BS 7837 DIN 4102 – Class B1 M2 Classification NFP 92-503 EN 13501-1 B-s3, d0 Total weight DIN and ISO 2286-2 – 650 gr/m ²
Flame retardant Polyester (FPTC420)	Any color	Flame retardant 420 gr/m ² . The fibers in this fabric provide extra security and protection. It is scorch, glow and spark resistant. Textile material that is flame retardant has an inhibiting effect on the occurrence of fire and slow fire spreading.	FPTC420 meets the following standards: Weight 420gr/m ² + 5% Standered width: 150 cm Tearing strenght: ±10% - Warp: 79N - Weft: 53N Tensile strength: ± 10% - Warp: 2800N/5 cm - Weft: 2232N/5 cm Watercolumn: ≥ 400mm Color fading level: GR6 ISO105B04-1994 Mildewtreated: Level 0 AATCC30-2017 Fireproof level: M2 BS7837-1996
Fixing		The inner tent hanging system is a unique system. It has no point loading, so the weight is equally distributed across the surface of the structure.	

Why choose us?

It's all in the detail. Our beautiful, sustainable glamping tents are not mass produced, but are created by a team of specialists with a passion for outdoor living. We personally manage every aspect, from the initial concept and product design, to the sourcing of eco-friendly materials and construction, to quality control. And it doesn't stop there, we provide ongoing service and support, long after you bought your tent or lodge.

Interested?

Get in touch to find out more about our tents, or come and see them for yourself. Email us on sales@yalacanvaslodges.com and we'll get right back to you or call us on +31 (0) 527 620 325.

